

Technical specifications

25.0 ECP

Product information

Range	ECP
Shape	Round
Tamper evident	No
Standard lid name	25.0 ECP DP
Seal lid name	25.0 ECP DS
Alternative lid name	25.0 ECP DF

Volume (+/- 1%) in liters

Volume under lid	17,6
Volume brim full	

Weight (+/- 3%) in grams

Bucket without handle	745
Standard lid	177
Seal lid	200
Alternative lid	200
Plastic handle (KBS*)	N/A
Plastic handle (KBKT*)	21
Steel handle (MB)	53
Steel handle with roller grip (GR)	56


* KBS: Hanging handle - KBKT: Handle on collar

Decoration

IML	No
-----	----

Packing

Standardpallet: 250 pieces Europallet: 225 pieces



Dimensions (+/- 1%) in millimeter

Diameter top	340
External diameter bottom	269
Height without lid	418
Height with standard lid	419

Raw material

Material	PP
PCR* availability	Yes

* Post-consumer recycled plastics

Performance

Stackability depends on many factors and any provided data is meant as an indication only. Consequently, users and/or packers should make internal trials to determine the viability of stacking and transportation.

Further information on page 2

Technical specifications

25.0 ECP

Specifications of use:

All Dijkstra Plastics products are suitable for all type of aqueous, acidic and alcoholic foods, foods which contain free fats at the surface and milk products.

Compliance:

All Dijkstra Plastics products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. The products are tested for 10 days at 60 °C which covers storage for above 6 months at room temperature and lower, including hotfill conditions and/or heating up to $70\text{ °C} \leq T \leq 100\text{ °C}$ for maximum $t = 120/2^{((T-70)/10)}$ minutes. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use. Before using the product make sure to read the specific "Declaration of Compliance according 10/2011". Products used for infants, pharmaceutical purposes and repeated use may require additional testing.

High temperatures:

The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging becomes flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. This packaging must be tested by users and/or packers with the actual product before approval for use at high temperatures.

Low temperatures:

Freezing conditions require special resins available on request. This packaging must be tested by the users and/or packers with the actual product before use at low temperatures.

Organoleptic characteristics:

The organoleptic properties can influence the product in the package. It is therefore important to properly test the organoleptic properties before use.

Shelf life:

The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low or very high temperatures over a longer period.

Quality information:

Deviations in the product specifications in this data sheet of 0,025% or less (i.e. 25 items per 100,000 pcs) are considered acceptable in the industry and therefore cannot be considered as a defect. Also, please refer to the General Sales and Delivery conditions in force at the time of delivery.